## **IN THE SPECIFICATION:**

Please replace [table 1] with the replacement [Table 1] that follows on the next page below.

[Table 1]

	Practical Examples						Comp
							Ex.
	1	2	3	4	5	6	1
α, ω — di	65.00	65.00	65.00	65.00	65.00	65.00	65.00
(triethoxysilylethylene)							
dimethylpolysiloxane; viscosity							
of 60,000 mPa•s							
α, ω —	35.00	35.00	35.00	35.00	35.00	35.00	35.00
dimethyldimethylpolysiloxane; viscosity of 100 mPa•s							
Precipitated calcium carbonate	100.00	100.00	100.00	100.00	100.00	100.00	100.00
Ground calcium carbonate	25.00	25.00	25.00	25.00	25.00	25.00	25.00
Methyltrimethoxysilane	2.80	2.80	2.80	2.80	2.80	2.80	2.80
Isobutyltrimethoxysilane	2.80	2.80	2.80	2.80	2.80	2.80	2.80
Titanium-di(isopropoxy)-	2.50	2.50	2.50	2.50	2.50	2.50	2.50
bis(ethylacetoacetate)							
γ-aminopropyltrimethoxysilane	0.33	0.33	0.33	0.33	0.33	0.33	0.33
γ-	0.66	0.66	0.66	0.66	0.66	0.66	0.66
glycidoxyropyltrimethoxysilane							
Trimethylsiloxy-capped	0.0009	0.018	0.045	0.073	0.108	1.053	-
polydimethylsiloxane (viscosity							
3,000 mPa•s)							
ZPT	0.0001	0.002	0.005	0.007	0.012	0.117	-
Concentration of ZPT (ppm) in	5	10	20	30	50	100	0
the weight of the entire						<u>500</u>	
composition							

(parts by weight)

ZPT is Zinc Pyrithion (bis(2-pyridylthio-1-oxide) zinc salt)

H&H No.: 71,051-038 - 2 -